

DUNLOP TILERS PRIMER



TECHNICAL SUMMARY

Size	1kg
Colour	Green/Blue
Description	Ready to use acrylic primer used as a bonding aid or for sealing porous backgrounds prior to tiling.
Coverage	1kg undiluted covers approx. 10m ² – on very porous backgrounds this may be less
Setting Time*	Allow 30 minutes between coats
Storage & Shelf Life	Stored between 5°C and 30°C and protected from frost the shelf life of this product is 12 months.

*depending on temperatures, background and site conditions

SITUATION

Walls	✓	The surface must be clean, dry, sound and flat. Used on plaster backgrounds when using a DUNLOP Cement based adhesives or where the background surface is porous.
Floors	✓	The surface must be clean, dry, sound and flat. Brush down highly polished surfaces before priming. NOTE ensure a even coat is applied, do NOT allow to form puddles on the surface. Ensure a Damp proof membrane is incorporated below direct to earth sub floors
Interior Dry	✓	
Exterior	✓	Ensure a Damp proof membrane is incorporated below direct to earth sub floors
Wet Areas	x	Background should be protected from water ingress. (e.g. by using Dunlop Shower Waterproofing Kit)
Power Showers	x	Background should be protected from water ingress. (e.g. by using Dunlop Shower Waterproofing Kit)
Swimming Pools	x	
Underfloor Heated Screeds	✓	The floor will need to be commissioned before tiling can be started. Contact DUNLOP TECHNICAL HELPLINE for more information
Electric Undertile Heating	✓	When used over a DUNLOP LX 360 FLOOR LEVELLER or heated screeds, floor background information below.

For further advice or advice on any other situations not listed above, please contact DUNLOP TECHNICAL HELPLINE on 01782 591120

BACKGROUND

Undiluted (neat) (2 coats and second applied 90° to the first) Allow to dry between coats.	✓	Use on the following backgrounds: ✓ Plaster walls when using a DUNLOP cement-based adhesive ✓ Tongued and grooved floorboards (before using a DUNLOP adhesive with DUNLOP PROCOVER uncoupling mat.
Diluted 1 part primer to 1 part clean water (1 coat of DUNLOP TILERS PRIMER)	✓	Use on the following backgrounds: ✓ Plaster walls when using a DUNLOP ready mixed adhesive, ✓ Cement/sand screeds and rendering ✓ Concrete
First coat diluted 1:1 with water and second coat Undiluted (neat) (2 coats and second applied 90° to the first) Allow to dry between coats.	✓	Use on the following backgrounds: ✓ Calcium sulphate screeds ✓ Anhydrite screeds Contact DUNLOP TECHNICAL HELPLINE for more information.
Undiluted or diluted 1:1 with water	✓	Used on the following sheets and boards: ✓ Fibre-reinforced cement boards ✓ Lightweight tile backer boards ✓ Calcium silicone boards NOTE always check with the board manufacturers recommendations for further guidance

For further advice or advice on any other backgrounds not listed above, please contact DUNLOP TECHNICAL HELPLINE on 01782 591120

IN A NUTSHELL

For sealing and priming substrates including porous backgrounds prior to tiling. DUNLOP TILERS PRIMER is a ready to use acrylic primer suitable for use on wall and floor surfaces prior to the application of Ceramic, Mosaic or Natural Stone Tiles in most interior and exterior situations including wet areas.

APPLICATION

Shake bottle before use. Apply 2 undiluted coats with a paintbrush on plaster, plasterboard, floorboards or screeds, or diluted with water 1:1 on plaster if using a ready mixed wall tile adhesive or on cement floors. Allow to dry for approx. 30 minutes between coats.

COVERAGE

1kg undiluted covers approx. 10m², on very porous backgrounds this may be less.

10 YEAR GUARANTEE

As a testament to the reliability and performance of our rigorous quality control procedures, all Dunlop products carry a 10-year guarantee. Subject to terms and conditions -see website for details www.dunloptrade.com

HEALTH & SAFETY INFORMATION

For detailed information on safety guidance, please refer to the Product Material Safety Data Sheet (available on request or via the Dunlop website www.dunloptrade.com)

DUNLOP TECHNICAL HELPLINE

For free expert guidance on the use of this product or any aspect of ceramic tiling telephone the DUNLOP TECHNICAL HELPLINE on: Tel: 01782 591120 Fax: 01782 591121.

Note: The customer must verify the suitability of any information, opinion, recommendation or advice ("Information") provided by the Company for the particular application for which any goods are intended to be used and the Company accepts no liability (whether in contract tort, or otherwise) whatsoever for any loss, damage, or expense arising from the misuse of any information it supplies nor for the use of any information in or for applications which are unsuitable or inappropriate. Building Adhesives Ltd operates a continuous research and development programme and reserves the right to alter or update information from time to time.